Dock Lift options for DL5-59M and DL6-59M

<u>Hinged Bridge plate</u> (one steel bridge with lifting chain included in base price)

Additional 18" x 60" steel bridge plate
Upgrade from 18" x 60" steel to Aluminum
Additional 18" x 60" Aluminum
Change to *Split* bridge plate
180 degree bridge plate

Approach Ramp

DL5-59M & DL6-59M

60" wide x 72" long x 8" height

(1/4" diamond tread plate)

Handrails

Upgrade to Aluminum Handrails

Night Locks

Mechanical wheel chock (120" min length required)

Bellows skirting

Roller shade

Electric

NEMA 1 WMPB control - No Cord (in lieu of std)
Up/Down key selector switch (in lieu of std)
Up/Down HHPB w/ key lockout (in lieu of std)
Up limitswitch (mounted & wired)
Flashing light
Warning bell, 2 second
NEMA 4 Quick Disc for control (plug & receptacle in box)

Power unit

5 hp 230/1/60 single phase power unit Power unit covers (Not NEMA rated) Oil Immersion heater

Hydraulic

Velocity fuses (in lieu of EFP)
Manual down valve
Additional Oil

Additional Hyd hose --- ½" diameter Additional Hyd hose --- ¾" diameter